

# IEC AC GB/T - TYPE2 CHARGING CABLE

## Introduction

Conform to the provisions and requirements of IEC 62196-2 IIb/GB/T 20234.2.  
Third Generation Technology without screw. Ergonomic design with modern  
appearance.

XLPO for cable insulation with better life span

TPU sheath improved the bending life and wear.

Applied with double color coating technology by customize color service.



## Feature

- IEC /GB/T Interface
- IP55
- 



## Material

- PC+PBT Alloy
- TPU
- Copper Alloy, Silver Plated
- Silicon Ruber

## Customized Color



Specification	Code	Current	Voltage	Cable Specification
AG-T-IG-32P	3011	32A	250V	3*6mm <sup>2</sup> +2*0.5mm <sup>2</sup>
AG-T-IG-32P-3P	3211	32A	440V	5*6mm <sup>2</sup> +2*0.5mm <sup>2</sup>

## IEC AC GB/T - TYPE2 CHARGING CABLE

Current	32A
Voltage	250V/440V
Charging Standard	IEC 62196-2,GB/T 20234.2

## CUSTOMIZATION

Cable Length	Yes ✓
Cable Color	Yes ✓
Plug Color	Yes ✓
Logo Printing	Yes ✓

## Mechanical Properties

Mechanical Life	No-load Plug>10000 times
Impact of External Force	1m Drop and 2T Vehicle Run Over
Flame Retardant Grade	UL94 V-0
Operating Temperature	-30°C~+50°C
Protection	IP55 IK08
Insertion Force	<100N

## Electrical Performance

Insulation Resistance	>1000MΩ (DC500V)
Pins Temperature Rise	<50K
Withstand Voltage	2500V
Contact Impedance	0.5 MΩ MAX