

EV Charging Spiral Cable



Introduction

It is generally made of TPU cable. The power connection used to control the movement of mobile devices can rebound quickly in a short time. It is widely used in mobile devices such as automobiles, machines, instruments and so on. According to the direction, there are mainly left direction coil spring and right direction coil spring.



Feature

- Conform to the provisions and requirements of 62196-2 IEC 2010
- Flexibility and Elasticity
- Non-toxic and Environment-friendly polymer
- High strength, Wear resistance, Cold resistance, High temperature resistance
- Oil resistance, Water resistance, Aging resistance

ltem	Outer diameter	Coiled Length	Cable Specifications
1	65±10MM	2750MM	5*6mm ² +2*0.5mm ²
2	50±10MM	3050MM	3*6mm²+2*0.5mm²
3	50±10MM	3050MM	5*2.5mm ² +2*0.5mm ²
4	45±10MM	2650MM	3*2.5mm ² +2*0.5mm ²

www.ag-elec.com Page 48-49

AG OEM/ODM Service

OEM: Original Equipment Manufacturing

Refers to the production in accordance with your specific conditions, all design drawings are completely in accordance with the design of your company to carry out manufacturing processing. OEM includes color, length, logo, packing, etc

ODM: Original Design Manufacturer/Private Labeling

It Means that the importer selects an already-existing product design from a factory catalog, makes a few small changes and sells it under their own brand name. Changes can include things like packaging or product bundles, colors and branding, and some limited adjustments to components or functionality. ODM includes product appearance design, function setting, new product development, etc

We provide flexible customized services with our abundant experiences in kinds of OEM and ODM

